

(12) **UK Patent Application** (19) **GB** (11) **2 243 381** (13) **A**
 (43) Date of A publication **30.10.1991**

(21) Application No **9108244.6**

(22) Date of filing **17.04.1991**

(30) Priority data
 (31) **513922** (32) **24.04.1990** (33) **US**

(71) Applicant
Structural Panels INC

(Incorporated In the USA - Florida)

**350 Burbank, Oldmar, Florida,
 United States of America**

(72) Inventor
Stephen C Meyerson

(74) Agent and/or Address for Service
Raworth Moss and Cook
36 Sydenham Road, Croydon, Surrey, CR0 2EF,
United Kingdom

(51) INT CL^a
E04B 1/66

(52) UK CL (Edition K)
**E1D DF112 DLEKM2 DLEQW2 D193 D2141 D401
 D402 D421 D501**

(56) Documents cited
GB 2142670 A GB 1347401 A GB 1277965 A
WO 86/05224 A US 4769963 A

(58) Field of search
**UK CL (Edition K) E1D DF112 DLEKMCV DLEKMDV
 DLEKMNV DLEKMSV DLEQWCV DLEQWDV
 DLEQWNV DLEQWSV
 INT CL^a E04B**

(54) Building panel joint

(57) A joint comprises, a ramp 20, pocket 18, which may contain a sealant (34, figures 9 and 10 not shown), an interlocking wedge element 19 and a centering stabilizer 21. In use two insulated panels 11 are locked together by a snap fit causing the wedge 19 to yieldably move over the ramp 20 into the pocket 18 causing the sealant (34), positioned in pocket 18, to extrude forming a gasket between the pocket walls 25 and the wedge 19. The wedge 19 may be formed on one edge of a panel, figure 8, or alternatively may be formed on both sides of an 'I' beam 42 interposed between two panels, figure 15.




FIG. 8




FIG. 15